

# Covaplus Vinyl Matt

## DESCRIPTION

Johnstone's Covaplus Vinyl Matt Emulsion is formulated for interior use on walls and ceilings. It provides a durable finish that is resistant to fading.

## RECOMMENDED USES

INTERIOR

Suitable for interior use.



## TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

## COLOUR RANGE

Over 15,500 colours are available via the Johnstone's CMS 2010 Tinting System.

## FINISH

Matt.

## VOLUME SOLID

27%

## COVERAGE

COVERAGE

12-14  
M<sup>2</sup>/LITRE

Approximately 12–14 square metres per litre depending on the nature and porosity of the surface.

## DRYING TIME

RECOAT

2-4  
HRS.

Touch dry in 1–2 hours.  
Recoat after 2–4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Minimal VOC content 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 3g/l VOC.

## FILM THICKNESS

Wet: 90µm, dry: 24µm.

## KEY PROPERTIES

- An attractive Vinyl Matt finish providing interior decoration and protection.
- Produces a wipeable finish.
- Excellent opacity and colour retention.
- EU Ecolabel accredited

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Covaplus Vinyl Matt Emulsion thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

## SIZES

1 Litre, 2.5 Litre, 5 Litre, 10 Litre.  
250ml testerpots & 1 Litre available in selected colours only.

## PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.