

Joncryl Water Based Primer Undercoat

DESCRIPTION

Johnstone's Joncryl is a high quality, acrylic resin based combined primer and undercoat formulated for interior and exterior use on new or bare wood, plaster, hardboard, cement and brickwork. It provides a low odour, quick drying, high opacity alternative to solvent-based primer and undercoat.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood, plaster, concrete, cement rendering, brickwork and blockwork.

COLOUR RANGE

Brilliant White

FINISH

Not applicable.

VOLUME SOLID

32%

COVERAGE



Approximately 12–14 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1 hour.
Recoat after 1–2 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Minimal VOC content 0-0.29%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).
This product contains max 3g/l VOC.

FILM THICKNESS

Wet: 77µm, dry: 24µm.

KEY PROPERTIES

- Quick drying, low odour application.
- Suitable for interior and exterior use on wood, plaster and masonry.
- A water-borne combined primer and undercoat based on a high quality acrylic resin.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare metal surfaces with the appropriate Johnstone's Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Do not apply in temperatures below 10°C or externally when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

1 Litre, 2.5 Litre, 5 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.