

Stormshield Smooth Masonry



DESCRIPTION

Johnstone's Stormshield Smooth Masonry is a premium quality, acrylic resin based paint formulated for exterior use on cement rendering, rough cast, brick and concrete. It provides a smooth finish that resists dirt accumulation and offers excellent weather resistance.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash etc.

COLOUR RANGE

Over 15,000 colours are available via the Johnstone's CMS 2010 Tinting System.

FINISH

Matt.

VOLUME SOLID

30%

COVERAGE



Approximately 9–11 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 4–6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 40g/l (2010).
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 30µm.

KEY PROPERTIES

- Expected life in excess of 15 years.
- A high quality, water-borne, acrylic resin based finish with excellent colour retention and anti-carbonation properties.
- Provides a durable smooth finish to exterior substrates.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Sterilisation Wash as directed. Stabilise surfaces of a highly porous or friable nature with Johnstone's Stormshield Stabilising Solution or Johnstone's Stormshield Quick Dry Stabilising Solution as directed. Wear a suitable face mask when creating dust.

For further advice contact Technical Advisory, on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

2.5 Litre, 5 Litre, 10 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.



The British Board of Agreement is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.