

# Vinyl Silk

## DESCRIPTION

Johnstone's Vinyl Silk Emulsion is formulated for interior use on walls and ceilings. It provides a durable sheen finish that is easy to clean and resistant to fading.

## RECOMMENDED USES

INTERIOR

Suitable for interior use.



## TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

## COLOUR RANGE

Over 15,500 colours are available via the Johnstone's CMS 2010 Tinting System.

## FINISH

Silk.

## VOLUME SOLID

31%

## COVERAGE

COVERAGE

10-12  
M<sup>2</sup>/LITRE

Approximately 10–12 square metres per litre, depending on the nature and porosity of the surface.

## DRYING TIME

RECOAT

3-4  
HRS.

Touch dry in 1–2 hours.  
Recoat after 3–4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## THINNER

Clean water.

## VOC CONTENT

Low VOC content 0.3–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/b): 100g/l (2010).  
This product contains max 80g/l VOC.

## FILM THICKNESS

Wet: 91µm, dry: 28µm.

## KEY PROPERTIES

- A high quality vinyl silk finish for interior walls and ceilings.
- Produces a washable surface.
- Especially suitable for embossed wallcoverings and areas where easy maintenance is required.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354100.

## APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Vinyl Silk thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

## SIZES

1 Litre\*\*, 2.5 Litre, 5 Litre, 10 Litre.

\*\* Only selected colours available in 1 Litre.

## PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.