

1.4 Super Leytex High Opacity Matt Emulsion



DESCRIPTION

A full bodied, quick drying, high opacity, matt finish for interior walls and ceilings. Ideal for work on new plaster, the permeable film has the added benefit of allowing new plaster surfaces to breathe and dry out.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

New plaster. Also suitable for use on aged plaster, wall boards, concrete, cement rendering, brickwork and blockwork in interior situations.

Colour range

Brilliant White and Magnolia. Additional pastel colours are available via the Leyland tinting system.

Finish

Matt

Volume solid

23%

Coverage

1 litre will cover approximately 13 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 1-2 hours. Recoatable after 2-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

Thinner

Clean water.

VOC content

LOW VOC CONTENT 0.30-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a):

75 g/l (2007) / 30 g/l (2010).

This product contains max 15 g/l VOC.

Film thickness

Wet: 90µm

Dry: 21µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Make good surface imperfections and cracks with Filler. Prime where required with the appropriate Leyland Primer. Rub down glossy surfaces with fine waterproof abrasive paper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of 1 part water to 9 parts Leyland Super Leytex High Opacity Matt Emulsion.

Application

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required apply a second coat after 2-4 hours. Do not apply in temperatures below 10°C.

Cleaning

Remove as much product as possible from application equipment before washing. Wash equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.